

# 40ft Storage Bitutainer™ Model TR-T-108 (For Direct Fire Heating)



TECCONTAINER  
SOLUTIONS

Suitable for Storage of Hot Liquid Bitumen,  
Bitumen Emulsions, PMBs and Heavy Fuel Oils

## Provides an Innovative and Versatile Concept in Temporary Bitumen Storage

- Nominal Capacity 65,000 Litres
- ISO 1496 Part 3 - Type 70 Classification
- High Performance factory fitted heating tubes
- Recirculation connection options available
- High Value Factory Installed Insulation and Pressed Corten Steel Outer Skin
- Fully Framed with Corner Twist Locks and Damage Reinforcement Plates
- Transported as a Standard 40 ft ISO Tank Container with Lloyds Approval
- Range of bitumen handling equipment available including pumps and hoses
- **Ideal for use as Individual Static Storage Tanks or as a part of an Interconnected Storage Facility System**



### Heating equipment required:

- Quick Fit Diesel Burners Set
- Stainless Steel Flame Liners

### Ratings:

Max GW 75,000 Kgs  
Payload 65,000 Kgs  
Tare Wt. <10,000 Kgs

### Measures:

Length 12,192 mm (40')  
Width 2,438 mm (8')  
Height 2,896 mm (9'6")