

24Mt IMO1 Rated Bitutainer™ Model TR-T-778 (For Direct Fire Heating)



Suitable for Storage and Fully Intermodal for Transportation of Hot Liquid Bitumen, Emulsions, Light and Heavy Fuel Oils

Fully IMDG Compliant with ADR/RID, US DOT/TC

- Nominal Capacity 24,000 Litres (Largest capacity IMO1 rated TEC Bitutainer™ available)
- ISO 1496 Part 3 - Type 75 “Tank Containers”
- Inner Vessel Pressure Tested to 4.0 bar
- High Performance factory fitted heating tubes
- Baffled design allows Partial Payloads to be carried
- High Value Factory Installed Insulation and Pressed Corten Steel Outer Skin
- Fully Framed with Corner Twist Locks and Damage Reinforcement Plates
- UN Coded T3 (IMO1 rated) Tank Container with Lloyds Approval
- Range of bitumen handling equipment available including pumps and hoses



Heating equipment required:

- Quick Fit Diesel Burner Set
- Stainless Steel Flame Liners

Ratings:

Max GW 30,480 Kgs
Payload 23,630 Kgs
Tare Wt. <6,850 Kgs

Measures:

Length 6,058 mm (20')
Width 2,438 mm (8')
Height 2,591 mm (8'6")